


Modular Sequence Valves

DGR-06-*2-52



▲ Service all units with F3 Seal Kit 919896

◆ Not available for sale.

Model	Cover	Plunger	Spool	Spring
DGR-06-A2-52				341612
DGR-06-B2-52	583190	593888		342243
DGR-06-D2-52			340305	
DGR-06-F2-52	583189	593899		342244
DGR-06-X2-52				341612
DGR-06-Y2-52	583190	—	340306	342243
DGR-06-Z2-52				342244



CAUTION

This valve cannot be used with pressure centered valves.

Note

When two or more modules are assembled together, this module must be mounted next to the subplate or mounting surface to accommodate the external drain ("Y" port).

Model Code

(F3) DGR - 06 - * 2 - 52

1 2 3 4 5 6

1 Seals

F3 - Seals for mineral oil and fire resistant fluids

3 Size

06 - 3/4 inch

5 Module Action

(Directly operated externally drained)

2 Model Series

DGR - Directional control, manifold or subplate mounted sequence module

4 Pressure Range

A - 80-250 psi
B - 125-500 psi
D - 250-1000 psi
F - 475-2000 psi
X - 10-30 psi
Y - 30-60 psi
Z - 60-125 psi

6 Design

For satisfactory service life of these components, use full flow filtration to provide fluid which meets ISO cleanliness code **20/18/15** or cleaner. Selections from Eaton OFP, OFR and OFRS filter series are recommended.

Printed in U.S.A.